

INDIANA



AgrowSil PRO™ Coarse-Sized Industrial Co-Product Agricultural Liming Material

Typical Lime Analysis (Dry Weight Basis)

Typical Percent Calcium	22.7 %	454 lb/T
Typical Percent Magnesium	5.7 %	114 lb/T
Typical Calcium Carbonate Equivalent (CCE)	95.3 %	
Sieve Analysis:		
Typical Percent Passing #8 Mesh Screen	81.2 %	
Typical Percent Passing #60 Mesh Screen	39.7 %	
Indiana Lime Quality Parameters		
Neutralizing Value (NV)	95.3 %	
Relative Neutralizing Value (RNV)	57.6 %	
Adjusted Lime Application Rate = Recommended Rate of Standard Lime X (60 / RNV)		

Recommended Application Rates: Specific recommendations for application rates to raise pH should be obtained from soil testing. Excessive application of AgrowSil PRO™ or any liming agent can result in soil pH higher than desirable for plant growth. For Spreaders: Bulk Density is 122 lbs/ft³

Storage Recommendations: Store AgrowSil PRO™ in a dry place not in direct contact with ground water or surface water. At agricultural sites, store only the amount of AgrowSil PRO™ that can be used during the current growing season.

Storage, transportation, and use of AgrowSil PRO™ shall be in a manner that will not create a nuisance or be harmful to public health, safety, or the environment or that will lead to excessive dispersal of AgrowSil PRO™ by wind or water erosion.

AgrowSil PRO™ is not to be used as an animal feed additive.

CAUTION: May cause eye and respiratory tract irritation. Avoid contact with eyes. Avoid breathing dust. Use with adequate ventilation.

Additional Information: Harsco Metals & Minerals guarantees that the AgrowSil PRO™ product characteristics listed above are verified to be in compliance at the time of production. AgrowSil PRO™ product is sampled as produced and is tested by an approved independent laboratory. Harsco Metals & Minerals cannot guarantee product characteristics (i.e. moisture, grain size) that are affected by long term storage or by improper care, handling, segregation, and storage by distributors or end users.

* AgrowSil PRO™ produced by Harsco Metals Americas.
Derived from Fused Silicates

* AgrowSil PRO™ is provided at as-produced typical moisture content of 10 %.

©2013 Harsco Metals Americas. All rights reserved. AGROWSIL is a registered trademark of Harsco Technologies, LLC.

3/18/15 Rev. 2



800 North Country Road
225, East Pittsboro, IN
Office: 317-892-2881
Fax: 317-892-2883